

Floodline Groundhog Mk II



The Floodline Groundhog Mk II is a self-contained, single-zone leak detection system which can be mounted vertically or horizontally. It can be connected to any control/building management system that has the facility to accept volt-free contacts.

Additional Floodline Point Sensors or Leak Detection Cable/Tape can be slaved off the Groundhog.

Function:
Water/Liquid detection

Zone Capacity:
1

Power:
Multi-voltage operation 12 or 24V AC or DC at 0.8watts

Construction:
Built into a stainless steel Guard Plate which provides protection and assists fixing

Dimensions:
L130 x W90 x D37 mm

Fixing:
Fixed or free-standing on floor or in drip tray
Vertically at base of wall or plant

Monitoring:
LEAK - continuous water/liquid built-in sensor and aux sensor input
SYSTEM FAULT - aux sensor or Leader Cable damage, failure or disconnection

Alarm Indicator:
Flashing LEDs for LEAK and SYSTEM FAULT
All alarms displayed separately and continuously until corrected and reset if in manual mode

Status Indicator:
Power LED

Controls:
Manual/Auto reset select
Sensitivity setting

Outputs:
Leak/system fault - SPCO Relay 1Amp@24Vdc



HUDDERSFIELD - FM512048

E&OE Rev 1.0

